

Marble Look

GLAZED PORCELAIN

BEST TILE® / BESTTILE.COM

Carrara

COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	CARRARA
12 x 24 Rectified	Matte	9.5 mm	1/8"	✓
	Polished	10.5 mm	1/8"	✓
24 x 24 Rectified	Matte	9.5 mm	1/8"	✓
	Polished	9.5 mm	1/8"	✓
24 x 48 Rectified	Matte	11 mm	1/8"	✓
	Polished	11 mm	1/8"	✓
.7 x 1.4 Herringbone Mosaic	Matte	11 mm	1/8"	✓
	Polished	11 mm	N/A	✓
2 x 3 Hexagon Mosaic	Matte	11 mm	N/A	✓
	Polished	11 mm	N/A	✓
3 x 8 Picket Mosaic	Matte	11 mm	N/A	✓
	Polished	11 mm	N/A	✓

✓ Stock Item. ⌚ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

ORIGIN: Brazil	<table border="1"> <thead> <tr> <th>RECOMMENDED APPLICATIONS</th> <th>R</th> <th>LC</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>FLOORS</td> <td>●</td> <td>●</td> <td></td> </tr> <tr> <td>WALLS / BACKSPLASH</td> <td>●</td> <td>●</td> <td>●</td> </tr> <tr> <td>POOL DECKING</td> <td></td> <td></td> <td></td> </tr> <tr> <td>EXTERNAL USE - FROST PROOF</td> <td>*</td> <td>*</td> <td></td> </tr> </tbody> </table>	RECOMMENDED APPLICATIONS	R	LC	C	FLOORS	●	●		WALLS / BACKSPLASH	●	●	●	POOL DECKING				EXTERNAL USE - FROST PROOF	*	*	
RECOMMENDED APPLICATIONS		R	LC	C																	
FLOORS		●	●																		
WALLS / BACKSPLASH		●	●	●																	
POOL DECKING																					
EXTERNAL USE - FROST PROOF	*	*																			
SHADE VARIATION: V3 - Moderate Variation																					
WEAR RATING: Class 4 - Rated for all residential and light commercial applications																					
It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.																					

● Approved for this application. * Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ASTM C373	≤ 0.5 %
Abrasion Resistance (Glazed)	ASTM C1027	4
Breaking Strength	ASTM C648	275
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42 (Matte); 0.30 (Polished)
Frost Resistance	ASTM C1026	Frost Proof
Chemical Resistance	ASTM C650	Class C
Scratch Hardness	MOHS	5 (Matte); 4 (Polished)

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.