

Beyond Terrazzo

COLOR BODY • GLAZED PORCELAIN

BEST TILE® / BESTTILE.COM

Create


COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	GREY	PEARL	SAND	WHITE
24 x 24 Micro	Matte	10 mm	1/8"	✓	✓	✓	✓
24 x 24 Medium	Matte	10 mm	1/8"	✓	✓	✓	✓
36 x 36 Micro	Matte	10 mm	1/8"	⊘	⊘	⊘	⊘
36 x 36 Medium	Matte	10 mm	1/8"	⊘	⊘	⊘	⊘
36 x 36 Maxi Deco	Matte	10 mm	1/8"	⊘			⊘
48 x 48 Micro	Matte	10 mm	1/8"	⊘	⊘	⊘	⊘
48 x 48 Medium	Matte	10 mm	1/8"	⊘	⊘	⊘	⊘
48 x 48 Maxi Deco	Matte	10 mm	1/8"	⊘			⊘

✓ Stock Item. ⊘ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

<p>ORIGIN: Italy</p> <p>SHADE VARIATION: V2 - Slight Variation</p> <p>WEAR RATING: Class 5 - Rated for all residential and commercial applications</p> <p>It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.</p> <p> Contains 25% Pre-Consumer Recycled Content.</p>	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS	●	●	●
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING	*	*	*
	EXTERNAL USE - FROST PROOF	*	*	*

● Approved for this application. * Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
Abrasion Resistance (Glazed)	ISO 10545-7	5
Breaking Strength	ISO 10545-4	≥ 45 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. Class GB
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Min. Class GB
Resistance to Stains	ISO 10545-14	Min. Class 3
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.