

Subway Tile

GLAZED CERAMIC

BEST TILE® / BESTTILE.COM

Villa

COLORS, SIZES & AVAILABILITY

| NOMINAL SIZE | FINISH | THICKNESS | GROUT JOINT | ACAVE | CARBON | COTTO | GLACIAL | GRIS | HIJAU GREEN | MARINE | OFF WHITE |
|--------------|--------|-----------|-------------|-------|--------|-------|---------|------|-------------|--------|-----------|
| 4 x 16 | Glossy | 7 mm | 3/16" | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

✓ Stock Item. ⚠ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

| ORIGIN: Brazil SHADE VARIATION: V3 - Moderate Variation WEAR RATING: 1 - Wall Applications Only It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile. | RECOMMENDED APPLICATIONS | R | LC | C |
|---|----------------------------|---|----|---|
| | FLOORS | Ⓜ | | |
| | WALLS / BACKSPLASH | ● | ● | ● |
| | POOL DECKING | | | |
| | EXTERNAL USE - FROST PROOF | | | |

● Approved for this application. * Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

| TECHNICAL FEATURE | NORMS | RESULTS |
|---|--------------|-----------|
| Water Absorption | ASTM C373 | ≤ 20 % |
| Abrasion Resistance (Glazed) | ASTM C1027 Ⓜ | 1 |
| Breaking Strength | ASTM C1027 | ≥ 125 lbs |
| Chemical Resistance - Household Chemicals | ASTM C650 | Class A |
| Resistance to Stains | MOHS | 4 |



Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.