


Iris | Ceramic / Porcelain




AVAILABLE SIZES




13x13




12x18



2x2 Mosaic



brick mosaic






2x12 Bullnose

DESCRIPTION

A contemporary approach to a classic look. Iris, our new porcelain series, emphasizes the marbleized look of stone throughout each piece. Imported from Spain, Iris Silver Blanco consists of large format glossy 12x18 wall tiles with coordinating 13x13 satin-finish, glazed porcelain floor tiles. A delicate 2x2 mosaic and small brick mosaic composed of stone, glass, and Mother of Pearl are available as accents for the Iris series. 2x12 bullnose completes the finishing touch!





COLORS

silver blanco




TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Material / Finish	Thickness
13 x 13		Glazed Porcelain - Satin	8 mm
12 x 18		Glazed Ceramic - Shiny	9 mm
2 x 2 Mosaic		Glazed Porcelain - Satin	8 mm
Brick Mosaic		Marble - Natural	8 mm

COORDINATING TRIM

Nominal	Shape	Finish	Thickness
2 x 12 Bullnose		Glazed Ceramic - Shiny	9 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	< 0.5%
PEI Abrasion Resistance (Glazed)	ISO 10545-7	5
Breaking Strength	ISO 10545-4	≥ 38 N/mm2
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GLA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GHA
Linear Thermal Expansion	ISO 10545-8	6.7 x 10 (-6)
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Class 5

SHADE VARIATION



V3 - MODERATE VARIATION
While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

Wall: 1 - Rated for wall applications only.
Floor: 5 - Rated for all residential and commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✗	✗	
WALLS / BACKSPLASH	✗	✗	✗
POOL DECKING			
EXTERNAL USE - FROST PROOF	✗		

✗ - Has been approved for this application.
* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.
Always inspect materials prior to installation.
Always mix 2-3 cartons at a time while installing to insure the best blend.