EastCoastTile.com





AVAILABLE SIZES

12x24 matte

11.625x23.3 polished

> 9x24 glossy wall

9x24 glossy brick wal

2x2 Mosaic matte

2x2 Mosaic polished


3x24 Bullnose matte

3x23.3 Bullnose polished

DESCRIPTION

Carrara, a Spanish porcelain tile, is an elegant recreation of the classic marble that offers a clean white background and soft grey veining. Choose from either a 12x24 matte or polished porcelain tile for both floor and wall tile installations. Matte finish is rated for all residential and light commercial applications, while polished finish is rated for all residential projects. The 9x24 glossy ceramic wall tile offers a traditional flat surface while the 4x8 brick pattern is beveled. 2x2 porcelain mosaics complement the floor along with 3x24 porcelain bullnose in both finishes.

COLORS









TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Material / Finish	Thickness
12 x 24		Porcelain / Matte	10 mm
11.625 x 23.3		Porcelain / Polished	10 mm
9 x 24 Wall		Ceramic / Glossy	10 mm
9 x 24 Brick Wall		Ceramic / Glossy	10.7 mm
2 x 2 Mosaic	000000 000000 000000 000000	Porcelain / Matte	10 mm
2 x 2 Mosaic	00000 00000 00000 00000 00000 00000	Porcelain / Polished	10 mm

COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3 x 24 Bullnose		Matte	10 mm
3 x 23.3 Bullnose		Polished	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	12x24, 2x2 MATTE	12x24, 2x2 POLISHED	9x24 WALL
Water Absorption	ISO 10545-3	< 0.5%	< 0.5%	NA
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4	3	1
Breaking Strength	ISO 10545-4	> 35N/ mm2	> 35N/ mm2	> 15N/ mm2
Static Coefficient of Friction Wet	C1028	> 0.50	> 0.50	NA
Dimensions Range	ISO 10545-2	Conforms	Conforms	Conforms
Frost Resistance	ISO 10545- 12	Frost Proof	Frost Proof	No
Chemical Resistance - Household Chemicals	ISO 10545- 13	GLA	GLA	GLA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545- 13	GLA	GLA	GLA
Scratch Hardness	MOHS	7	5	NA

SHADE VARIATION



V2 - SLIGHT VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

Matte Finish: 4 - Rated for all residential and light commercial applications.

Polished Finish: 3 - Rated for all residential applications.

Glossy Finish: 1 - Rated for wall applications only.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	×	×	
WALLS / BACKSPLASH	×	×	×
POOL DECKING			
EXTERNAL USE - FROST PROOF	Matte Only		
		las baan annuavad f	ov this application

X - Has been approved for this application.* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.

