

Durban | Glazed Porcelain



AVAILABLE SIZES



DESCRIPTION


Reinvent Traditional. Inspired by the charm of hand-scraped plank floors, comes the arrival of our most authentic wood-inspired porcelain series, Durban. Imported from Italy, Durban 8x48 glazed porcelain is available in five natural wood tones and is suitable for all residential and light commercial applications, even wet areas!

COLORS



TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
8 x 48		Matte	10.8 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	$E \leq 0.5\%$ Bla GL
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	$S \geq 1300$ N
Static Coefficient of Friction Wet	C1028	≥ 0.60
Dynamic Coefficient of Friction Wet	AcuTest	0.47
Dimensions Range	ISO 10545-2	$\pm 0.5\%$ Max
Warpage	C485	$\pm 0.4\%$
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GLA
Scratch Hardness	MOHS	8.5
Linear Thermal Expansion	ISO 10545-8	Test Method Available
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

SHADE VARIATION



V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

4 - Rated for all residential and light commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✘	✘	
WALLS / BACKSPLASH	✘	✘	✘
POOL DECKING			
EXTERNAL USE - FROST PROOF	✘	*	

✘ - Has been approved for this application.
* - Information is available upon request.

NOTES

The factory recommends staggering Durban no more than 25% the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.