







Series W | Glazed Porcelain




AVAILABLE SIZES

-  3x6
-  12x12
-  2x2 Mosaic
-  12x24
-  18x18
-  3.25 x 12 Bullnose

DESCRIPTION






Inspired by the beauty of marble, onyx and limestone, Series W blends together all three stone looks to create an exquisite glazed porcelain line. With an array of wall and floor sizes to choose from, Series W offers the most sought after formats including 12x12, 12x24 and 18x18 as well as 3x6, 2x2, and 3x12 trim. Available in four rich colors; Walnut, Silver, Dust and Land, Series W is a one of a kind idea worthy of its admiration.

COLORS




TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
3 x 6		Matte	10 mm
12 x 12		Matte	10 mm
2 x 2 Mosaic		Matte	10 mm
12 x 24		Matte	10 mm
18 x 18		Matte	10 mm

COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3.25 x 12 Bullnose		Matte	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	< 0.1 %
PEI Abrasion Resistance (Glazed)	ISO 10545-7	5
Breaking Strength	ISO 10545-4	> 2000 N
Static Coefficient of Friction Wet	C1028	≥ 0.60
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GLA
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

SHADE VARIATION



V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

5 - Rated for all residential and commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✘	✘	✘
WALLS / BACKSPLASH	✘	✘	✘
POOL DECKING			
EXTERNAL USE - FROST PROOF	✘	*	*

✘ - Has been approved for this application.
* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.