



Heartwood Glazed Porcelain

AVAILABLE SIZES

12x24

DESCRIPTION

An authentic blend of a signature wood-look design. Introducing Heartwood, a contemporary glazed porcelain design from our wood-look collection. A combination of natural tones and distinct textures creates a signature piece of art in each 12 x 24 format. Layered with personality, Heartwood focuses on fusing together multiple wood-look strips to develop a diversion from ordinary wood styles. Resilience to wet areas and low maintenance appeal offer benefits that real wood can't compete with. Heartwood is now available in four ultra urban tones.

COLORS









TECHNICAL INFORMATION

TILE SIZES

| Nominal | Shape | Finish | Thickness |
|---------|-------|------------------|-----------|
| 12 x 24 | | Textured - Matte | 10 mm |

PERFORMANCE DATA

| CHARACTERISTIC | NORMS | RESULTS |
|---|--------------|-------------|
| Water Absorption | ISO 10545-3 | < 0.5% |
| PEI Abrasion Resistance (Glazed) | ISO 10545-7 | 4 |
| Breaking Strength | ISO 10545-4 | > 35N/mm2 |
| Static Coefficient of Friction Wet | C1028 | > 0.60 |
| Dimensions Range | ISO 10545-2 | Conforms |
| Frost Resistance | ISO 10545-12 | Frost Proof |
| Chemical Resistance - Household Chemicals | ISO 10545-13 | GLA |
| Chemical Resistance - Low Concentration of Acids and Bases | ISO 10545-13 | GLA |
| Scratch Hardness | MOHS | 7 |

SHADE VARIATION



V2 - SLIGHT VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

4 - Rated for all residential and light commercial applications.

APPLICATIONS

| | RESIDENTIAL | LIGHT COMMERCIAL | COMMERCIAL |
|----------------------------|-------------|---------------------|------------|
| FLOORS | × | × | |
| WALLS / BACKSPLASH | × | × | × |
| POOL DECKING | * | | |
| EXTERNAL USE - FROST PROOF | * | * | |

✗ - Has been approved for this application.

* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.