

# Sandalwood | Glazed Ceramic



## AVAILABLE SIZES



## DESCRIPTION

The Best Tile Sandalwood ceramic collection replicates the appearance of wood planks with an artistic approach. At \$2.79 a square foot, Sandalwood offers unique contemporary appeal at an affordable price tag! Imported from Spain, Sandalwood is a red body tile available in three stunning colors on a 9x26 wide plank format. Sandalwood is appropriate for floor and wall use, in residential and light commercial applications.

## COLORS

beige



gris




taupe



# TECHNICAL INFORMATION

## TILE SIZES

Nominal	Shape	Finish	Thickness
9 x 26		Matte	9.8 mm

## PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	3% < E ≤ 6%
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	> 32N/mm <sup>2</sup>
Static Coefficient of Friction Wet	C1028	≥0.65
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	No
Chemical Resistance - Household Chemicals	ISO 10545-13	GLA/GHA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GLA/GHA
Linear Thermal Expansion	ISO 10545-8	6.4x10 <sup>(-6)</sup>
Thermal Shock Resistance	ISO 10545-9	Conforms
Resistance to Stains	ISO 10545-14	Class 5

## SHADE VARIATION



### V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

## WEAR CODE

4 - Rated for all residential and light commercial applications.

## APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✘		
WALLS / BACKSPLASH	✘	✘	
POOL DECKING			
EXTERNAL USE - FROST PROOF			

✘ - Has been approved for this application.

\* - Information is available upon request.

## NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.