





AVAILABLE SIZES

5x30

10x30

3x24 Bullnose

DESCRIPTION

Introducing a multi-stone look that is rich in character, with a clean, subtle texture. Verse Italian porcelain blends the unique look of marble, travertine, quartzite, limestone, and cement on a high-quality colored-body plank format. Available in 5x30 and 10x30 with coordinating trim, Verse is one our most contemporary European tile selections. Available in four color ranges and suitable for all floor and wall tile applications in residential and commercial spaces.

COLORS



chestnut









TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
5 x 30		Matte	10 mm
10 x 30		Matte	10 mm

COORDINATING TRIM

Nominal	Shape	Finish	Thickness
3 x 24 Bullnose		Matte	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS	
Water Absorption	ISO 10545-3	0.05%	
PEI Abrasion Resistance (Glazed)	ISO 10545-7	NA	
Breaking Strength	ISO 10545-4	Conforms	
Dynamic Coefficient of Friction Wet	C1028	0.61	
Static Coefficient of Friction Wet	C1028	≥ 0.60	
Dimensions Range	ISO 10545-2	Conforms	
Frost Resistance	ISO 10545-12	Frost Proof	
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant	
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Resistant	
Thermal Shock Resistance	ISO 10545-9	Resistant	
Resistance to Stains	ISO 10545-14	Cleanable	

SHADE VARIATION



V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

5 - Rated for all residential and commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	×	×	×
WALLS / BACKSPLASH	×	×	×
POOL DECKING	*	*	
EXTERNAL USE - FROST PROOF	×	×	

x - Has been approved for this application.

* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

