




# Rodas | Ceramic / Porcelain



## AVAILABLE SIZES



## DESCRIPTION

The Rodas collection is a high quality floor and wall combination with intriguing Spanish tile sizes and screens. This luxurious marbleized design is available in a ceramic 10"x20" wall and 13"x13" floor format. Enhance your design with a 2"x2" mesh-mounted mosaic, made of glazed porcelain and suitable for shower floors. Select from four traditional color options with coordinating trim (wall use only).

## COLORS

beige








gris



marengo






marron




# TECHNICAL INFORMATION

## TILE SIZES

Nominal	Shape	Material	Thickness
10 x 20		Glazed Ceramic	9.5 mm
13 x 13		Glazed Ceramic	8.5 mm
2 x 2 Mosaic		Glazed Porcelain	8.5 mm

## COORDINATING TRIM

Nominal	Shape	Material	Thickness
2 x 10 Bullnose		Glazed Ceramic	9.5 mm

## PERFORMANCE DATA

CHARACTERISTIC	NORMS	CERAMIC	PORCELAIN
Water Absorption	ISO 10545-3	3% < E ≤ 6%	≤ 0.5%
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4	4
Breaking Strength	ISO 10545-4	> 1100 N	≥ 3500 N
Static Coefficient of Friction Wet	C1028	0.65	0.65
Frost Resistance	ISO 10545-12	No	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GA	GA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GLA/GHA	GLA/GHA
Scratch Hardness	MOHS	3	NA
Resistance to Stains	ISO 10545-14	Class 5	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resists	Resists

## SHADE VARIATION



V3 - MODERATE VARIATION  
While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

## WEAR CODE

13x13 / 2x2 Mosaic: 4 - Rated for all residential and light commercial applications.  
10x20 / 2x10 Bullnose: 1 - Rated for wall applications only.

## APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✗	✗	
WALLS / BACKSPLASH	✗	✗	✗
POOL DECKING			
EXTERNAL USE - FROST PROOF			

✗ - Has been approved for this application.  
\* - Information is available upon request.

## NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.  
Always inspect materials prior to installation.  
Always mix 2-3 cartons at a time while installing to insure the best blend.