

Mora Medley Glazed Porcelain

AVAILABLE SIZES

12x24

DESCRIPTION

Mora Medley is like nothing you've ever seen in glazed porcelain before! This beautiful Spanish 12x24 tile replicates small pencil-like pieces of stone molded together to create a medley of color and texture. The textured surface and modern approach to a "stone look" enhances any room with a unique aesthetic.

COLORS

















TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness
12 x 24		Textured - Matte	10 mm

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	< 0.5%
PEI Abrasion Resistance (Glazed)	ISO 10545-7	3/4/5
Breaking Strength	ISO 10545-4	> 35N/mm2
Static Coefficient of Friction Wet	C1028	0.63
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GLA
Scratch Hardness	MOHS	7

SHADE VARIATION



BLACK / WHITE: V1 - UNIFORM APPEARANCE

Differences among pieces from the same production run are minimal.



GREY MIX: V2 - SLIGHT VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.



ALL OTHER COLORS: V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

Ivory, Sand, White: 5 - Rated for all residential and commercial applications.

Black, Cream, Grey Mix, Hazel: 4 - Rated for all residential and light commercial applications.

Dark: 3 - Rated for all residential applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	×	×	
WALLS / BACKSPLASH	×	×	×
POOL DECKING	*	*	
EXTERNAL USE - FROST PROOF	×	*	

x - Has been approved for this application.

* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.