



# Pietra Alpi | Ceramic



## AVAILABLE SIZES

- 4x8
- 4x12
- 8x12
- 12x12
- 3x8 bullnose

## DESCRIPTION

Pietra Alpi is a ceramic floor and wall tile series replicating the classic, sophisticated look of white Carrara marble. Its high-tech digital screen offers a realistic interpretation of muted grey veining on a sharp white marble background. Wall tiles are available in three versatile formats: a 4"x12" matte finish, a beveled 4"x8" glossy finish, or an 8"x12" format in either glossy or matte finishes. The 12"x12" floor tile is available in a luxurious satin finish. Trim is available for all wall sizes.

## COLORS


white



glossy



matte



glossy








matte





matte

# TECHNICAL INFORMATION

## TILE SIZES

| Nominal            | Shape   | Finish | Thickness |
|--------------------|---|--------|-----------|
| 4 x 8 Beveled Wall |  | Glossy | 7.7 mm    |
| 4 x 12 wall        |  | Matte  | 7.2 mm    |
| 8 x 12 wall        |  | Glossy | 7.2 mm    |
| 8 x 12 wall        |  | Matte  | 7.2 mm    |
| 12 x 12 floor      |  | Matte  | 8.1 mm    |

## COORDINATING TRIM

| Nominal        | Shape   | Finish | Thickness |
|----------------|---|--------|-----------|
| 3 x 8 Bullnose |  | Glossy | 7.2 mm    |
| 3 x 8 Bullnose |  | Matte  | 7.2 mm    |

## PERFORMANCE DATA

| CHARACTERISTIC   | NORMS        | RESULTS<br>(12x12 Only) |
|--|--------------|-------------------------|
| Water Absorption   | ISO 10545-3  | 0.07 %                  |
| PEI Abrasion Resistance (Glazed)                           | ISO 10545-7  | 4                       |
| Breaking Strength  | ISO 10545-4  | ≥ 250 lbf               |
| Dynamic Coefficient of Friction Wet                        | AcuTest      | 0.5                     |
| Chemical Resistance - Household Chemicals                  | ISO 10545-13 | Class E                 |
| Chemical Resistance - Low Concentration of Acids and Bases | ISO 10545-13 | Class E                 |
| Resistance to Stains                                       | ISO 10545-14 | Class A                 |

## SHADE VARIATION



### V2 - SLIGHT VARIATION

Clearly distinguishable differences in texture and/or pattern within similar colors.

## WEAR CODE

12x12 Floor: 4 - Rated for all residential and light commercial applications.

All other sizes: 1 - Rated for wall applications only.

## APPLICATIONS

|                            | RESIDENTIAL | LIGHT<br>COMMERCIAL | COMMERCIAL |
|----------------------------|-------------|---------------------|------------|
| FLOORS                     | 12x12 Only  | 12x12 Only          |            |
| WALLS / BACKSPLASH         | ✘           | ✘                   | ✘          |
| POOL DECKING               |             |                     |            |
| EXTERNAL USE - FROST PROOF |             |                     |            |

✘ - Has been approved for this application.

\* - Information is available upon request.

## NOTES

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.