



## Ravenna | Glazed Porcelain



### AVAILABLE SIZES




10x10




2x2 Mosaic




10x20




10x20 Concept



20x20



2x11 Listel



2x10 Bullnose





3x20 Bullnose

### DESCRIPTION

Ravenna is a Spanish porcelain series that captures the timeless look of Carrara marble. Crisp white background and subtle grey veining is brought to life on three modular formats with soft, chiseled edges: 10"x10", 10"x20" and 20"x20". Combine with either a 2"x2" mosaic or a 10"x20" decorative option to create a true sense of elegance. Ravenna is available at competitive pricing for a top quality porcelain and is suitable for all residential and light commercial applications.







### COLORS

blanco





# TECHNICAL INFORMATION

## TILE SIZES

Nominal	Shape	Finish	Thickness
10 x 10		Matte	9 mm
2 x 2 Mosaic		Matte	9 mm
10 x 20		Matte	9 mm
10 x 20 Concept		Matte	9 mm
20 x 20		Matte	9 mm
2 x 11 Listel		Matte	9 mm

## COORDINATING TRIM

Nominal	Shape	Finish	Thickness
2 x 10 Bullnose		Matte	9 mm
3 x 20 Bullnose		Matte	9 mm

## PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 %
PEI Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≥ 43 N/mm2
Dynamic Coefficient of Friction Wet	AcuTest	0.46
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Scratch Hardness	MOHS	5
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resists

## RECYCLED CONTENT



Contains 35% Recycled Content.

## SHADE VARIATION



V2 - SLIGHT VARIATION  
Clearly distinguishable differences in texture and/or pattern within similar colors.

## WEAR CODE

4 - Rated for all residential and light commercial applications.

2x11 Listel: 1 - Rated for wall applications only.

## APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✗	✗	
WALLS / BACKSPLASH	✗	✗	✗
POOL DECKING	*		
EXTERNAL USE - FROST PROOF	✗		

✗ - Has been approved for this application.  
\* - Information is available upon request.

## NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.